



Pacific Wood Laminates, Inc.

CONCRETE FORMS	WORKING SURFACE	PANEL DESIGN	FORM SYSTEM	RELEASE AGENTS	* POUR RANGE
PROFACE ALKA-MAX™ G1S only 117 LB/MS, 570 G/SM	<ul style="list-style-type: none"> High Resin Melamine Overlay Superior Alkalinity & abrasion resistance High gloss finish 	<ul style="list-style-type: none"> Proprietary hardwood Struc 1 equivalent Minimal grain transfer 	<ul style="list-style-type: none"> Produced for max re-uses Best in gang & engineered systems 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Engin. Syst. 85+ Gang Forms 40+ Job Built 20+
PROFACE PSF HAO™ G1S only 122 LB/MS, 597 G/SM	<ul style="list-style-type: none"> High Alkaline Overlay Exceptional resistance to alkalinity & moisture Semi-gloss finish 	<ul style="list-style-type: none"> Proprietary hardwood Struc 1 equivalent Minimal grain transfer 	<ul style="list-style-type: none"> Produced for max re-uses Best in gang & engineered systems 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Engin. Syst. 85-225 Gang Forms 25-80 Job Built 20-60
PROFACE HDO™ 100/30 120/30 109 LB/MS, 535 G/SM	<ul style="list-style-type: none"> Premium High Density Overlay Resists moisture & wear Semi-gloss finish 	<ul style="list-style-type: none"> Proprietary hardwood Struc 1 equivalent Minimal grain transfer 	<ul style="list-style-type: none"> Specifically designed for multiple re-uses Best in gang & engineered systems 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Engin. Syst. 75-200 Gang Forms 20-75 Job Built 15-50
MULTIFORM PSF HAO™ G1S only 122 LB/MS, 597 G/SM	<ul style="list-style-type: none"> High Alkaline Overlay Exceptional resistance to alkalinity & moisture Semi-gloss finish 	<ul style="list-style-type: none"> Struc 1 Balanced construction 	<ul style="list-style-type: none"> Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Gang Forms 20-60 Job Built 10-20
MULTIFORM HDO™ 100/30 120/30 109 LB/MS, 535 G/SM	<ul style="list-style-type: none"> Durable High Density Overlay Resists moisture & wear Smooth finish 	<ul style="list-style-type: none"> Struc 1 Balanced construction 	<ul style="list-style-type: none"> Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Gang Forms 10-30 Job Built 10-20
PROFACE MDO EF™ 77 LB/MS, 398 G/SM	<ul style="list-style-type: none"> Premium Enhanced Flow Overlay Resists moisture & wear Smooth finish 	<ul style="list-style-type: none"> Proprietary hardwood Struc 1 equivalent Minimal grain transfer Good one or two side available 	<ul style="list-style-type: none"> Specifically designed for multiple re-uses Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete Utility Release applied at mill 	<u>APPROXIMATE</u> Gang Forms 20-50 Job Built 15-40
PROFORM MDO EF™ 77 LB/MS, 398 G/SM	<ul style="list-style-type: none"> Enhanced Flow Overlay Resists moisture & wear Smooth finish 	<ul style="list-style-type: none"> Struc 1 Balanced construction Good one or two side available 	<ul style="list-style-type: none"> Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete Utility Release applied at mill 	<u>APPROXIMATE</u> Gang Forms 12-30 Job Built 7-15
PROFACE MDO™ 74 LB/MS, 362 G/SM	<ul style="list-style-type: none"> Provides a superior matte finish Resists wear 	<ul style="list-style-type: none"> Proprietary hardwood Struc 1 equivalent Minimal grain transfer Good one or two side available 	<ul style="list-style-type: none"> Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete Utility Release applied at mill 	<u>APPROXIMATE</u> Gang Forms 10-30 Job Built 10-20
PROFORM MDO™ 74 LB/MS, 362 G/SM	<ul style="list-style-type: none"> Provides a durable, matte finish 	<ul style="list-style-type: none"> Struc 1 Balanced construction Good one or two side available 	<ul style="list-style-type: none"> Best in gang & job built forms 	<ul style="list-style-type: none"> Nox-Crete Utility Release applied at mill 	<u>APPROXIMATE</u> Gang Forms 10-20 Job Built 5-10
ELITE PROFACE PSF™ G1S only 26 LB/MS, 115 G/SM	<ul style="list-style-type: none"> Durable PSF Overlay Resists moisture & wear Semi-gloss finish 	<ul style="list-style-type: none"> Proprietary hardwood Mill option 5, 6, or 7 ply 	<ul style="list-style-type: none"> Best in job built forms or cut up applications 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Job Built 5-10
ELITE HDO™ 100/30 120/30 109 LB/MS, 535 G/SM	<ul style="list-style-type: none"> Durable High Density Overlay Resists moisture & wear Semi-gloss finish 	<ul style="list-style-type: none"> Struc 1 or Class 1 Cost effective alternative to MultiForm HDO 	<ul style="list-style-type: none"> Best in job built forms or cut up applications 	<ul style="list-style-type: none"> Nox-Crete RA #10 coating not applied at mill 	<u>APPROXIMATE</u> Job Built 5-10
ELITE MDO™ 77 LB/MS, 398 G/SM	<ul style="list-style-type: none"> Resists moisture & wear Matte finish 	<ul style="list-style-type: none"> Struc 1 or Class 1 Cost effective alternative to Proform MDO Good one or two side available 	<ul style="list-style-type: none"> Best in job built forms or cut up applications 	<ul style="list-style-type: none"> Nox-Crete Utility Release applied at mill 	<u>APPROXIMATE</u> Job Built 4-8

All thicknesses available from 3/8 through 1 1/8, including MM sizes.

Form system recommendations, pricing & special sizing available upon request.

All 1 Step Lay-up, standard 4X8 Dimension, made in USA, APA Stamp PS-1, available in 5 & 7 ply.

Each of our panels are edge sealed with Nox-Crete Edge Flex 645.

*All pour ranges are approximate, performance depends on proper use and care of panels.



chemical solutions to concrete problems

